

Material Safety Data Sheet

N/A=Not Applicable

NE=Not Established

Date Prepared: 06-20-2000

PRODUCT IDENTIFICATION

Product Name: Stain Magic for Wool "Part B"
Generic Name: Stain Magic for Wool B
Supplier's Name: CTI Chemical Technologies International
Supplier's Address: PO Box 968, Rancho Cordova, CA 95741

Chemical Family: Stain Remover
Formula:
Phone Number: (916) 638-1315
Emergency: (800) 424-9300

Hazardous Materials Identification

Health	
Flammability	
Reactivity	
Special	

MATERIAL IDENTIFICATION AND INFORMATION

CHEMICAL NAME	CAS NO.	OSHA-PEL	ACGIH-TLV	Other
Trade Secret	N/A	2mg/m3	2mg/m3	NIOSH 2mg/m3

PHYSICAL DATA

Boiling Range: N/A **Freezing/Melting:** N/A
Vapor Pressure: N/A **Vapor Density:** N/A
%Volatile: **pH:** 13
Solubility in Water: soluble **Evaporation Rate:** NA
Physical Description: Clear liquid with strong odor

REACTIVITY DATA

Stability: stable at room temp. & atmospheric pressure
Incompatibility (Materials to Avoid): some components of this mixture are not compatible with strong oxidizers, strong acids, and some metals.
Hazardous Decomposition Products: NH₃ gas, carbon oxides
Hazardous Polymerization: will not occur

FIRE AND EXPLOSION HAZARD DATA

Concentrate Flash Point (Method): **Explosive Limits**
Propellant Flash Point (Method): **Upper:** N/A
Flash Point (Method): **Lower:** N/A
Extinguishing Media: Dry chemical, or CO₂.
Special Fire Fighting Procedures: Use water (only to cool) nearby containers and structures exposed to fire. Direct water stream may spread fire. Fire fighters should wear a self contained, positive pressure breathing apparatus and full protective clothing. (NICSH/MSHA approved). Isolate fire area and deny entry.

STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storage:
For use by professionals only. Avoid breathing vapors. Always ensure good ventilation of surroundings during use. Always keep container lid tightly closed and properly labels. Wash thoroughly after handling. Loosen closures cautiously. Store in cool dry place. Storage pressure: Atmospheric. Avoid excessive heat or pressure. Avoid storage with oxidizing agents, acids

HEALTH HAZARDS AND FIRST AID

Effect of Overexposure:

Primary Route of Entry:

Skin: Exposure may cause skin irritation, drying, chapping.

Eyes: Vapors may irritate eyes. Direct or prolonged contact with eyes will be painful and irritating may also cause possible permanent damage.

Inhalation: Inhalation will cause irritation to the respiratory tract

Ingestion: If swallowed will cause GI irritation.

Other: Sensory irritation

First Aid Procedures: Get medical attention immediately.

Skin: Flush thoroughly with cool water while removing contaminated clothes.

Eyes: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue.

Inhalation: Remove to fresh air. If breathing is difficult have trained person administer oxygen. If breathing stops administer artificial respiration.

Ingestion: Do not induce vomiting. If directed by medical professional, give large quantities of water and if available give several glasses of milk.

SPECIAL PROTECTION INFORMATION

Respiratory Protection: These precautions are not usually necessary in adequately ventilated areas. Wear NIOSH/MSHA approved respirator when ventilation is not adequate.

Wear protective clothing to minimize skin contact. Wash skin after use. Wash contaminated clothing and dry before reuse.

Other Protective Equipment: One should always use chemicals with an awareness of the potential hazard of the effect on the human system. To minimize employee exposure to all chemicals, including this product, use good industrial hygiene practices.

Ventilation: Always ensure adequate ventilation.

Eye Protection: Wear safety goggles to protect against contact when appropriate.

SPILL OR LEAK PROCEDURES

Steps to be Taken in Case Material is Released or Spilled:

Small Spills – Wipe or mop up and dispose of in DOT approved container. Wear protective clothing.

Large Spills – Contain by diking with soil or other non-combustible sorbent material, then dispose into DOT container. Contain all spills or leaks to prevent discharge into the environment.

The statements, technical information and recommendations contained herein are believed to be reliable and accurate; however, these are provided without warranty or guarantee of any kind, express or implied, as to their accuracy or completeness. As the conditions or methods of use are beyond our control, the manufacturer and seller do not assume any responsibility and expressly disclaim and liability for use of this product. This information is offered for your information, consideration and investigation. You should satisfy yourself that you have all current data relevant to your particular use.

Waste Disposal Method:

Dispose of in DOT approved waste container.

Do not dump into storm drains, sanitary sewers or any body of water.